

Spray Truck Applicator



STANDARD FEATURES

- ✓ Stainless Steel Product Tank
- ✓ Stainless Steel Tank Piers And Tank Bands
- √ 600, 800, 1000, and 1280 Gallon Capacities
- √ 60 Foot All Hydraulic Booms
- ✓ 20" Spacing With Triple Nozzle Bodies
- √ 5 Boom Sections
- √ Flow Based Electronic Control System
- ✓ 2" or 3" Suction Tank Outlets To Pump
- ✓ 2" Tank Agitation With Electric Adjustment Valve
- √ 16" Tank Manhole
- ✓ Hydraulic Driven Product Pump
- ✓ Stainless Steel Induction Hopper With Rinse Nozzle
- ✓ Product Tank Rinse System
- ✓ Joystick Controls For Hydraulic Booms
- ✓ Stainless Steel Walk Boards
- ✓ LED Lights

OPTIONS

- √ Foam Marker System
- ✓ GPS Guidance System
- ✓ Automatic Boom Control
- ✓ Tilt Compensator For GPS System
- √ Fence Row Nozzle
- ✓ Electronic Individual Nozzle Shut-off
- ✓ Electronic PSI Transducer

GENERAL FERTILIZER EQUIPMENT, INC.

429 EDWARDIA DRIVE - PO BOX 19409 - GREENSBORO, NC 27419 - 800 277-4337



FEATURES OF THE SPEEDY SPREAD Spray Truck Applicator





Electronic Flow Controls With Boom Switchbox And Joystick Boom Control



60 Foot Tubular Construction Booms With Hydraulic Tip Fold Breakaways



Hydraulic Driven Product Pump



Hydraulic Driven Tank Rinse Pump



Stainless Steel Walk Boards With Rails



Hydraulic Boom Height Adjustment